

850 Mirage Semi Transparent is a light filtering farbic providing excellent heat and glare control with good insulation for comfort all year



## 850 Mirage Semi Transparent

## Benefits

**850 Mirage** is a semi transparent, light filtering fabric offering a subtle texture with a distinct, soft touch. Provides excellent heat and glare control with good insulation for comfort all year round

850 Mirage is part of the Verosol Core Collection - fabrics developed in Europe, to the highest quality standard.

A semi transparent fabric suitable for Roller Blinds, Pleated Blinds and Panel Glide Systems.

## Care Instructions

For regular maintenance, a soft feather duster or vacuum-cleaning with a soft brush in a low setting.

## Further Information

To find out more information phone Verosol Customer Care on 1800 721 404 or visit www.verosol.com.au



# 850 Mirage Semi Transparent

### **Technical Information**

| Fabric Density            | Semi Transparent                                      |                            |                         |  |
|---------------------------|---|----------------------------|-------------------------|--|
| Composition               | 100% Trevira CS                                       |                            |                         |  |
| Weight per m <sup>2</sup> | 132g ± 5%   |                            |                         |  |
| Thickness                 | 0.30mm  |                            |                         |  |
| Width                     | Pleats — 2200mm ± 50mm                                |                            | Rollers — 2400mm ± 50mm |  |
| Anti-microbial            | ASTM-E2149-01   |                            |                         |  |
| Flame Retardancy          | ISO 6941  | DIN 4102-Classification B1 |                         |  |
| Suitable Products         | Roller Blinds, Pleated Blinds and Panel Glide Systems |                            |                         |  |

| Fabric colour code           | 0000 |
|------------------------------|------|
| Solar transmittance          | 42%  |
| Solar reflectance outside    | 52%  |
| Solar absorbtance            | 6%   |
| Luminous transmittance [VLT] | 37%  |
| UV transmittance             | 19%  |
| Openness factor (nominal)    | 2%   |
| Ra (colour rendering index)  | 97   |

### Glazing Type - Single 4mm Clear Glass

| Visible light transmittance [VLT]     | 41% |
|---------------------------------------|-----|
| G-value / Solar heat gain coefficient | 43% |
| Shading coefficient                   | 49% |
| U-value (W/m²K)                       | 2.7 |

## Glazing Type - High Performance Glazing

| Visible light transmittance [VLT]     | 30% |
|---------------------------------------|-----|
| G-value / Solar heat gain coefficient | 22% |
| Shading coefficient                   | 25% |
| U-value (W/m²K)                       | 0.9 |

## Colour Range





0105 Natural













