Verosol



982 Originals Metallised Blockout

Features

982 Originals is a polyester blockout fabric with a metal backing that provides total privacy and room darkening. Providing excellent protection against summer heat and superb insulation in winter. Woven to 2200mm wide, 982 is perfectly designed for when room darkening and total privacy is desired.

982 Originals is part of the Verosol Core Collection - metallised fabrics developed in Europe, to the highest quality standard.

A blockout fabric suitable for Roller Blinds and Pleated Blinds.

Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, a soft feather duster or vacuum-cleaning with a soft brush in a low setting.

Further Information

To find out more information phone Verosol Customer Care on 1800 721 404 or visit www.verosol.com.au



982 Originals Metallised Blockout

Technical Information

Fabric Density	Blockout		
Composition	100% Polyester		
Weight per m ²	270g ± 5%		
Thickness	0.34mm		
Width	2200mm		
Colour Fastness	Colour >5 DIN 54004 Metal 8		
Anti Static	Anti static, PVC and Formaldehyde free		
Anti-microbial	ASTM-E2149-01		
Flame Retardancy	Fabric is non fire retardant		
Aluminium Adhesion	ISO 2409	Classification 0	
Corrosion Resistance	Metal layer EN ISO 3231		
Suitable Products	Roller Blinds and Pleated Blinds		

Fabric colour code	0000
Solar transmittance	0%
Solar reflectance outside	65%
Solar absorbtance	35%
Luminous transmittance [VLT]	0%
UV transmittance	0%
Openness factor (nominal)	0

Glazing Type - Single 4mm Clear Glass

Visible light transmittance [VLT]	0%
G-value / Solar heat gain coefficient	24%
Shading coefficient	28%
U-value (W/m²K)	2.0

Glazing Type - High Performance Glazing

Visible light transmittance [VLT]	0%
G-value / Solar heat gain coefficient	17%
Shading coefficient	20%
U-value (W/m²K)	0.8

Colour Range





0998 Anthracite 0829 Onyx















© Copyright 2014 Verosol Australia [ABN 36 006 221 003]

Version 1 | Issued March 2014

Information supplied was current at time of printing. All presented data calculated in WIS 3.0.1 (Advanced Windows Information System) with spectral data. Specifications and other data are based on information available at the time of preparation of this document and are subject to production tolerances and/or change without prior notice. Flame retardancy information is sourced from AWTA testing results. Please note that test results may vary slightly depending on fabric colour. [4mm Single Glass reference glazing A EN 14501], [High Performance Glazing reference glazing D EN 14501] according to EN 14500.