

# Ambience Hardwood Shutter

# Verosol



## Operation

**S206.0** Ambience Hardwood Shutter System

## Features

The Ambience Hardwood shutter features a light weight frame with a concealed aluminium control rod which allows for full closure of blades in two positions. This provides clear and uninterrupted visibility through the blades.

Available with elliptical blades in 64mm and 89mm, painted shutters are made from finger jointed Poplar, coated using a polyurethane coating system. Stained shutters are made from basswood, which are stained and then coated using a nitro-cellulose lacquer system.

A range of functional, quality hardware is supplied with the Ambience Hardwood shutter, providing you with the complete package.

## Ambience Hardwood Shutter

|                       |   |   |   |
|-----------------------|---|---|---|
| Applications          | Ambience Hardwood Shutter   |   |   |
| Material              | Premium Poplar and Premium Basswood   |   |   |
| Available sizes       | Width range   | 400mm Minimum - 1050mm Maximum  | Single and Hinged Shutter Systems         |
|                       |   | 400mm Minimum - 600mm Maximum   | Double Hinged Shutter System              |
|                       |   | 700mm Minimum - 1050mm Maximum  | Sliding Shutter System                    |
|                       |   | 400mm Minimum - 600mm Maximum   | Bi-Fold Shutter System                    |
|                       | Height range  | 400mm Minimum - 3000mm Maximum  |   |
| Max area              |   | 3.15m <sup>2</sup>  | Single, Hinged and Sliding Shutter System |
|                       |   | 1.8m <sup>2</sup>   | Double Hinged and Bi-Fold Shutter System  |
| Elliptical blade size | Width   | 64mm    89mm  |   |
|                       | Reveal depth  | 57mm    70mm  | Single, Hinged and Double Hinged Shutter  |
| Operation             | Single, Hinged, Double Hinged, Sliding and Bi-Fold System   |   |   |
| Mid rail position     | Mandatory for all shutters over 1800mm in drop  |   |   |
|                       | Specify height of mid rail to centre and note if critical mid rail height is required   |   |   |
| Split controls        | Blades spanning over 1200mm in drop will have a control rod split in half - specify if you require the split at a specific height |   |   |
| Control and handle    | Type  | Aluminium control rod   |   |
|                       | Operation   | Operation by rear push stick control or blades  |   |
| Finishes              | Paint   | Poplar hardwood coated with a polyurethane coating system<br>White, Silk White, Shell, Ivory and Alabaster                          |   |
|                       | Timber Grain  | Stained and coated with a nitro-cellulose lacquer system<br>Natural, Light Oak, Sugar Maple, Cherry, Walnut, Black Walnut and Wenge |   |
|                       | Speciality colours  | Special paints can be made to order   |   |
|                       |   |   |   |

## Colour Range

|  |   |   |   |   |   |   |   |   |  |   |   |
|--|---|---|---|---|---|---|---|---|--|---|---|
|  |  |  |  |  |  |  |  |  |  |  |  |
| White<br>P100  | Ivory<br>P103   | Shell<br>P104   | Silk White<br>P105  | Alabaster<br>P107   | Natural<br>B200   | Light Oak<br>B201   | Sugar<br>Maple<br>B202  | Cherry<br>B204  | Wenge<br>B209  | Walnut<br>B209  | Black<br>Walnut<br>B206   |